

TYRES

| Product group | Tyres |
|-----------------|------------------|
| Item number | 15711728 |
| Valid tyre size | 10.0 / 75 - 15.3 |
| LI / SI / PR | 123 A8, 10 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | AW 909 V-Line |



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction.
- Good handling characteristics, both on the road and in the field.



Technical Informations

| Item number | 15711728 |
|------------------------------|------------------|
| EAN | 8903094010394 |
| Valid tyre size | 10.0 / 75 - 15.3 |
| LI / SI / PR | 123 A8, 10 PR |
| TL/TT | TL |
| Brand | ВКТ |
| Tread pattern | AW 909 V-Line |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 14,08 |
| Recommended rim size | 9.00 |
| Maximum air pressure [bar]. | 3,90 |
| Section width (mm) | 274 |
| Outer diameter of tyre [mm]. | 760 |
| Stat. radius (SLR) [mm] | 343 |
| Rolling circumference [mm]. | 2227 |
| Tread depth (mm) | 9,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 123 A8 | 1550 | 40 | | 3,90 | LLV |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.