

TYRES

Product group	Tyres
Item number	15711753
Valid tyre size	10.0 / 75 - 15.3
LI / SI / PR	123 A8 / 135 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15711753
EAN	8903094027422
Valid tyre size	10.0 / 75 - 15.3
LI / SI / PR	123 A8 / 135 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	24,19
Recommended rim size	9.00
Maximum air pressure [bar].	7,10
Section width (mm)	264
Outer diameter of tyre [mm].	785
Stat. radius (SLR) [mm]	360
Rolling circumference [mm].	2404
Tread depth (mm)	23,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
123 A8	1550	40	Drive Wheel	7,10	LLV
135 A8	2180	40	Free Rolling	7,10	LLV