Bohnenkamp Moving Professionals

15.11.2024

TYRES

Product group	Tyres	
Item number	15711759	
Valid tyre size	11.5 / 80 - 15.3	
LI / SI / PR	119 A8 / 131 A8, 10 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	MP 567	



Notes and features

- The BKT MP 567 is a multi purpose tyre offering maximum flexibility.
- The tyre features good traction in all weathers.
- Suitable for on- and off-road use.

- The open tread pattern allows for efficient self-cleaning.
- Suitable for use on vehicles such as Unimogs, backhoe loaders, dumpers, etc.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15711759
EAN	8903094057580
Valid tyre size	11.5 / 80 - 15.3
LI / SI / PR	119 A8 / 131 A8, 10 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	MP 567
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	29,28
Recommended rim size	9.00
Maximum air pressure [bar].	3,40
Section width (mm)	292
Outer diameter of tyre [mm].	868
Stat. radius (SLR) [mm]	393
Rolling circumference [mm].	2578
Tread depth (mm)	21,5
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
119 A8	1360	40	Drive Wheel	3,40	LLV
131 A8	1950	40	Free Rolling	3,40	LLV

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.