

TYRES

Product group	Tyres
Item number	15711788
Valid tyre size	11.5 / 80 - 15.3
LI / SI / PR	131 A8, 10 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	AW 909 V-Line



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction.
- Good handling characteristics, both on the road and in the field.



Technical Informations

Item number	15711788
EAN	8903094010585
Valid tyre size	11.5 / 80 - 15.3
LI / SI / PR	131 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 909 V-Line
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	20,11
Recommended rim size	9.00
Maximum air pressure [bar].	3,40
Section width (mm)	297
Outer diameter of tyre [mm].	844
Stat. radius (SLR) [mm]	370
Rolling circumference [mm].	2473
Tread depth (mm)	8,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
131 A8	1950	40		3,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.