

TYRES

Product group	Tyres
Item number	15711790
Valid tyre size	11.5 / 80 - 15.3
LI / SI / PR	131 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

Technical Informations

Item number	15711790
EAN	8903094009367
Valid tyre size	11.5 / 80 - 15.3
LI / SI / PR	131 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	21,89
Recommended rim size	9.00
Maximum air pressure [bar].	3,40
Section width (mm)	297
Outer diameter of tyre [mm].	844
Stat. radius (SLR) [mm]	370
Rolling circumference [mm].	2473
Tread depth (mm)	10,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
131 A8	1950	40		3,40	