

## TYRES

Product group	Tyres
Item number	15711805
Valid tyre size	280 / 60 - 15.5
LI / SI / PR	102 A8 / 115 A8, 8 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 678



## Notes and features

- The TR 678 is suitable for use on excavators and loaders as well as for the agricultural sector with its special, steel belt version.
- The tyre is characterised by its good traction and excellent self-cleaning.
- The cut-resistant tread compound reduces the risk of machinery downtimes and increases efficiency.

## Technical Informations

Item number	15711805
EAN	8903094019922
Valid tyre size	280 / 60 - 15.5
LI / SI / PR	102 A8 / 115 A8, 8 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 678
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	22,29
Recommended rim size	8.0
Permitted rim size	8.25
Maximum air pressure [bar].	2,90
Section width (mm)	275
Outer diameter of tyre [mm].	750
Stat. radius (SLR) [mm]	357
Rolling circumference [mm].	2250
Tread depth (mm)	20,5
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
102 A8	850	40	Drive Wheel	2,90	LLV
115 A8	1215	40	Free Rolling	2,90	LLV