

TYRES

Product group	Tyres	
Item number	15711817	
Valid tyre size	340 / 55 - 16	
LI / SI / PR	121 A8 / 133 A8	
TL/TT	TL	
Brand	BKT	
Tread pattern	AW 729	





Notes and features

- The BKT AW 729 is an implement tyre for agricultural trailers, hay harvesters, balers and soil tillage implements
- The rounded tyre shoulder and the tread pattern with 3 circumferential grooves in the tread centre ensure low soil compaction and prevent soil damage
- The tyre offers excellent performance in both field applications and on the road



Technical Informations

Item number	15711817
EAN	8903094066117
Valid tyre size	340 / 55 - 16
Alternative size 1	13.0/55-16
LI / SI / PR	121 A8 / 133 A8
TL/TT	TL
Brand	BKT
Tread pattern	AW 729
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	28,14
Recommended rim size	11.0
Maximum air pressure [bar].	3,20
Section width (mm)	343
Outer diameter of tyre [mm].	785
Stat. radius (SLR) [mm]	358
Rolling circumference [mm].	2358
Tread depth (mm)	13,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
121 A8	1450	40	Drive Wheel	3,20	
133 A8	2060	40	Free Rolling	3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.