

## TYRES

Product group	Tyres
Item number	15711820
Valid tyre size	400 / 60 - 15.5
LI / SI / PR	145 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 708



## Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction.
- Good handling characteristics, both on the road and in the field.

## Technical Informations

Item number	15711820
EAN	8903094010318
Valid tyre size	400 / 60 - 15.5
LI / SI / PR	145 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 708
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	34,63
Recommended rim size	13.00
Maximum air pressure [bar].	4,90
Section width (mm)	405
Outer diameter of tyre [mm].	875
Stat. radius (SLR) [mm]	380
Rolling circumference [mm].	2564
Tread depth (mm)	12,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40		4,90	