

TYRES

Product group	Tyres
Item number	15711823
Valid tyre size	6.00 - 16
LI / SI / PR	83 A8 / 95 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 504



Bohnenkamp
Moving Professionals



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15711823
EAN	8903094019168
Valid tyre size	6.00 - 16
LI / SI / PR	83 A8 / 95 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	9,33
Recommended rim size	4.00E
Permitted rim size	4.50E, 4.50K
Maximum air pressure [bar].	2,80
Section width (mm)	164
Outer diameter of tyre [mm].	735
Stat. radius (SLR) [mm]	343
Rolling circumference [mm].	2190
Tread depth (mm)	18,0
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
83 A8	487	40	Drive Wheel	2,80	LLV
95 A8	690	40	Free Rolling	2,80	LLV