

TYRES

Product group	Tyres
Item number	15711825
Valid tyre size	6.00 - 16
LI / SI / PR	95 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	AW 702



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

Technical Informations

Item number	15711825
EAN	8903094009862
Valid tyre size	6.00 - 16
LI / SI / PR	95 A8, 6 PR
TL/TT	TT
Brand	BKT
Tread pattern	AW 702
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	8,36
Recommended rim size	4.00
Permitted rim size	4.50
Maximum air pressure [bar].	2,75
Section width (mm)	169
Outer diameter of tyre [mm].	722
Stat. radius (SLR) [mm]	337
Rolling circumference [mm].	2150
Tread depth (mm)	8,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
95 A8	690	40	Free Rolling	2,75	LLV