

TYRES

Product group	Tyres
Item number	15711828
Valid tyre size	7.50 - 16
LI / SI / PR	99 A8 / 112 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 504



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15711828
EAN	8903094019328
Valid tyre size	7.50 - 16
LI / SI / PR	99 A8 / 112 A8, 8 PR
TL/TT	TT
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	13,36
Recommended rim size	5.50F
Permitted rim size	4.50E, 5.0F, 4.00E, 5K, 6LB, 6.00F
Maximum air pressure [bar].	3,20
Section width (mm)	209
Outer diameter of tyre [mm].	803
Stat. radius (SLR) [mm]	372
Rolling circumference [mm].	2475
Tread depth (mm)	22,0
Number of lugs	19x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
98 A8	750	40	Drive Wheel	3,20	LLV
112 A8	1120	40	Free Rolling	3,20	LLV