Bohnenkamp Moving Professionals

22.09.2024

TYRES

Product group	Tyres	
Item number	15711829	
Valid tyre size	7.50 - 16	
LI / SI / PR	99 A8 / 112 A8, 8 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	AS 504	



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Bohnenkamp Moving Professionals

Technical Informations

Item number	15711829	
EAN	8903094019335	
Valid tyre size	7.50 - 16	
LI / SI / PR	99 A8 / 112 A8, 8 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	AS 504	
Antistatic	No	
Tyre colour	Black	
ECE regulation number	ECE 106	
Nettogewicht [kg] (gültig)	14,45	
Recommended rim size	5.50F	
Permitted rim size	4.00E, 4.50E, 5.00F, 5K, 6LB, 6.00F	
Maximum air pressure [bar].	3,20	
Section width (mm)	209	
Outer diameter of tyre [mm].	803	
Stat. radius (SLR) [mm]	372	
Rolling circumference [mm].	2475	
Tread depth (mm)	22,0	
Number of lugs	19x2	
E-Ready	No	

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
99 A8	775	40	Drive Wheel	3,20	LLV
112 A8	1120	40	Free Rolling	3,20	LLV

22.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.