

## TYRES

Product group	Tyres
Item number	15711830
Valid tyre size	10.5 / 65 - 16
LI / SI / PR	123 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

## Technical Informations

Item number	15711830
EAN	8903094009237
Valid tyre size	10.5 / 65 - 16
LI / SI / PR	123 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	16,71
Recommended rim size	9
Maximum air pressure [bar].	3,80
Section width (mm)	270
Outer diameter of tyre [mm].	760
Stat. radius (SLR) [mm]	343
Rolling circumference [mm].	2112
Tread depth (mm)	10,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
123 A8	1550	40	Free Rolling	3,80	LLV