

TYRES

Product group	Tyres
Item number	15711834
Valid tyre size	14.0 / 65 - 16
LI / SI / PR	142 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 705



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

Technical Informations

Item number	15711834
EAN	8903094009930
Valid tyre size	14.0 / 65 - 16
LI / SI / PR	142 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 705
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	28,82
Recommended rim size	11
Maximum air pressure [bar].	4,00
Section width (mm)	353
Outer diameter of tyre [mm].	870
Stat. radius (SLR) [mm]	388
Rolling circumference [mm].	2549
Tread depth (mm)	12,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 A8	2650	40	Free Rolling	4,00	LLV