

TYRES

Product group	Tyres
Item number	15711836
Valid tyre size	13.0 / 75 - 16
LI / SI / PR	135 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

Technical Informations

Item number	15711836
EAN	8903094025640
Valid tyre size	13.0 / 75 - 16
LI / SI / PR	135 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	29,05
Recommended rim size	11.0
Maximum air pressure [bar].	3,00
Section width (mm)	340
Outer diameter of tyre [mm].	890
Stat. radius (SLR) [mm]	396
Rolling circumference [mm].	2726
Tread depth (mm)	12,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 A8	2180	40	Free Rolling	3,00	LLV