

TYRES

Product group	Tyres
Item number	15711841
Valid tyre size	380 / 55 R 16.5
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	BKT
Tread pattern	AW 711



Bohnenkamp
Moving Professionals



Notes and features

- Modern implement tyre for trailers and other agricultural machines for various applications
- Can be mounted tubeless
- Rounded tyre shoulder to protect crops and soil
- Approved up to 50 km/h, low rolling resistance

Technical Informations

Item number	15711841
EAN	8903094044757
Valid tyre size	380 / 55 R 16.5
LI / SI / PR	150 A8 / 150 B
TL/TT	TL
Brand	BKT
Tread pattern	AW 711
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	38,65
Recommended rim size	12
Permitted rim size	11.75
Maximum air pressure [bar].	5,00
Section width (mm)	360
Outer diameter of tyre [mm].	830
Stat. radius (SLR) [mm]	372
Rolling circumference [mm].	2500
Tread depth (mm)	9,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A8	3350	40		5,00	
150 B	3350	50		5,00	