

TYRES

Product group	Tyres
Item number	15711842
Valid tyre size	15.0 / 55 - 17
LI / SI / PR	134 A8, 10 PR
TL/TT	TL
Brand	ВКТ
Tread pattern	AW 909 V-Line





Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction.
- Good handling characteristics, both on the road and in the field.



Technical Informations

Item number	15711842
EAN	8903094010752
Valid tyre size	15.0 / 55 - 17
LI / SI / PR	134 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 909 V-Line
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	24,91
Recommended rim size	13.00
Permitted rim size	13
Maximum air pressure [bar].	2,60
Section width (mm)	391
Outer diameter of tyre [mm].	850
Stat. radius (SLR) [mm]	377
Rolling circumference [mm].	2490
Tread depth (mm)	10,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 A8	2120	40		2,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.