

## **TYRES**

Product group	Tyres	
Item number	15711847	
Valid tyre size	15.0 / 55 - 17	
LI / SI / PR	141 A8, 14 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	AW 705	





## Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field



## **Technical Informations**

Item number	15711847
EAN	8903094010066
Valid tyre size	15.0 / 55 - 17
LI / SI / PR	141 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 705
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	30,39
Recommended rim size	13.00
Maximum air pressure [bar].	3,70
Section width (mm)	381
Outer diameter of tyre [mm].	850
Stat. radius (SLR) [mm]	391
Speed Radius Index (SRI)	410
Rolling circumference [mm].	2575
Tread depth (mm)	12,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 A8	2575	40		4,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.