

TYRES

Product group	Tyres
Item number	15711848
Valid tyre size	15.0 / 55 - 17
LI / SI / PR	146 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 705



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

Technical Informations

Item number	15711848
EAN	8903094010097
Valid tyre size	15.0 / 55 - 17
LI / SI / PR	146 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 705
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	34,22
Recommended rim size	13.00
Maximum air pressure [bar].	4,70
Section width (mm)	381
Outer diameter of tyre [mm].	850
Stat. radius (SLR) [mm]	391
Speed Radius Index (SRI)	410
Rolling circumference [mm].	2575
Tread depth (mm)	12,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 A8	3000	40	Free Rolling	4,70	LLV
	2060	40	Drive Wheel	4,70	LLV