

TYRES

Product group	Tyres
Item number	15711850
Valid tyre size	15.0 / 55 - 17
LI / SI / PR	134 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	Rib 774 (B)



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT RIB 774 (B) is a low-profile tyre for various agricultural implements.
- Thanks to its rib tread pattern, it is suitable for field and road use.

Technical Informations

Item number	15711850
EAN	8903094010936
Valid tyre size	15.0 / 55 - 17
LI / SI / PR	134 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	Rib 774 (B)
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	29,23
Recommended rim size	13.00
Permitted rim size	13
Maximum air pressure [bar].	2,60
Section width (mm)	391
Outer diameter of tyre [mm].	850
Stat. radius (SLR) [mm]	377
Rolling circumference [mm].	2490
Tread depth (mm)	10,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 A8	2120	40		2,60	