

TYRES

Product group	Tyres
Item number	15711853
Valid tyre size	15.0 / 55 - 17
LI / SI / PR	122 A8 / 134 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 729



Notes and features

- The BKT AW 729 is an implement tyre for agricultural trailers, hay harvesters, balers and soil tillage implements
- The rounded tyre shoulder and the tread pattern with 3 circumferential grooves in the tread centre ensure low soil compaction and prevent soil damage
- The tyre offers excellent performance in both field applications and on the road

Technical Informations

Item number	15711853
EAN	8903094065387
Valid tyre size	15.0 / 55 - 17
LI / SI / PR	122 A8 / 134 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 729
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	29,96
Recommended rim size	13.00
Permitted rim size	13, W13
Maximum air pressure [bar].	2,60
Section width (mm)	385
Outer diameter of tyre [mm].	850
Stat. radius (SLR) [mm]	377
Rolling circumference [mm].	2560
Tread depth (mm)	12,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 A8	1500	40	Drive Wheel	2,60	
134 A8	2120	40	Free Rolling	2,60	