

TYRES

Product group	Tyres
Item number	15711860
Valid tyre size	15.0 / 55 - 17
LI / SI / PR	122 A8 / 134 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15711860
EAN	8903094018833
Valid tyre size	15.0 / 55 - 17
LI / SI / PR	122 A8 / 134 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	33,78
Recommended rim size	13.00
Permitted rim size	13
Maximum air pressure [bar].	2,60
Section width (mm)	380
Outer diameter of tyre [mm].	890
Stat. radius (SLR) [mm]	395
Rolling circumference [mm].	2608
Tread depth (mm)	23,0
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
122 A8	1500	40	Drive Wheel	2,60	LLV
134 A8	2120	40	Free Rolling	2,60	LLV