

TYRES

Product group	Tyres
Item number	15711866
Valid tyre size	420 / 55 - 17
LI / SI / PR	121 A8 / 133 A8
TL/TT	TL
Brand	BKT
Tread pattern	AW 726



Notes and features

- The BKT726 was specially developed for use on agricultural trailers and soil cultivating machines
- It is suitable for use in the field as well as for road transport journeys
- On the road, the tyre is characterised by a very good performance, ride comfort and self-cleaning properties

Technical Informations

Item number	15711866
EAN	8903094055647
Valid tyre size	420 / 55 - 17
LI / SI / PR	121 A8 / 133 A8
TL/TT	TL
Brand	BKT
Tread pattern	AW 726
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	39,70
Recommended rim size	13.00
Maximum air pressure [bar].	2,00
Section width (mm)	415
Outer diameter of tyre [mm].	890
Stat. radius (SLR) [mm]	392
Rolling circumference [mm].	2584
Tread depth (mm)	13,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
121 A8	1450	40	Drive Wheel	2,00	
133 A8	2060	40	Free Rolling	2,00	