

TYRES

Product group	Tyres
Item number	15711867
Valid tyre size	420 / 55 - 17
LI / SI / PR	133 A8 / 145 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15711867
EAN	8903094032136
Valid tyre size	420 / 55 - 17
LI / SI / PR	133 A8 / 145 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	44,95
Recommended rim size	13.00
Maximum air pressure [bar].	3,50
Section width (mm)	430
Outer diameter of tyre [mm].	910
Stat. radius (SLR) [mm]	407
Rolling circumference [mm].	2712
Tread depth (mm)	19,8
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40	Drive Wheel	3,50	LLV
145 A8	2900	40	Free Rolling	3,50	LLV