

## **TYRES**

| Product group   | Tyres                  |  |
|-----------------|------------------------|--|
| Item number     | 15711870               |  |
| Valid tyre size | 10.5 / 80 - 18         |  |
| LI / SI / PR    | 119 A8 / 131 A8, 10 PR |  |
| TL/TT           | TL                     |  |
| Brand           | ВКТ                    |  |
| Tread pattern   | AS 504                 |  |





## Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting



## **Technical Informations**

| Item number                  | 15711870               |
|------------------------------|------------------------|
| EAN                          | 8903094018628          |
| Valid tyre size              | 10.5 / 80 - 18         |
| LI / SI / PR                 | 119 A8 / 131 A8, 10 PR |
| TL/TT                        | TL                     |
| Brand                        | BKT                    |
| Tread pattern                | AS 504                 |
| Antistatic                   | No                     |
| Tyre colour                  | Black                  |
| ECE regulation number        | ECE 106                |
| Nettogewicht [kg] (gültig)   | 29,95                  |
| Recommended rim size         | 9                      |
| Permitted rim size           | 8                      |
| Maximum air pressure [bar].  | 3,70                   |
| Section width (mm)           | 274                    |
| Outer diameter of tyre [mm]. | 907                    |
| Stat. radius (SLR) [mm]      | 405                    |
| Rolling circumference [mm].  | 2657                   |
| Tread depth (mm)             | 22,0                   |
| E-Ready                      | No                     |

## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 119 A8 | 1360               | 40           | Drive Wheel   | 3,70                        | LLV          |
| 131 A8 | 1950               | 40           | Free Rolling  | 3,70                        | LLV          |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.