

TYRES

Product group	Tyres	
Item number	15711877	
Valid tyre size	10.5 / 80 - 18	
LI / SI / PR	138 A8, 14 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	AW 702	





Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field



Technical Informations

Item number	15711877
EAN	8903094009343
Valid tyre size	10.5 / 80 - 18
LI / SI / PR	138 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	25,96
Recommended rim size	9
Maximum air pressure [bar].	5,10
Section width (mm)	275
Outer diameter of tyre [mm].	885
Stat. radius (SLR) [mm]	395
Speed Radius Index (SRI)	425
Rolling circumference [mm].	2593
Tread depth (mm)	11,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 A8	2360	40		5,10	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.