

TYRES

Product group	Tyres
Item number	15711878
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	129 A8 / 142 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 461



Bohnenkamp
Moving Professionals



Notes and features

- The BKT TR 461 is a versatile MPT tyre.
- It is suitable for application on municipal tractors as well as on telehandlers and backhoe loaders.
- Sidewall protectors guarantee good resistance against cuts and other damages and provide puncture protection.
- The construction of the tyre also provides excellent stability.

Technical Informations

Item number	15711878
EAN	8903094028344
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	129 A8 / 142 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	TR 461
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	45,38
Recommended rim size	W9
Permitted rim size	11
Maximum air pressure [bar].	3,70
Section width (mm)	305
Outer diameter of tyre [mm].	987
Stat. radius (SLR) [mm]	435
Rolling circumference [mm].	2902
Tread depth (mm)	27,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
129 A8	1850	40	Drive Wheel	3,70	LLV
142 A8	2650	40	Free Rolling	3,70	LLV