

TYRES

Product group	Tyres
Item number	15711886
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	148 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

Technical Informations

Item number	15711886
EAN	8903094009701
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	148 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	34,77
Recommended rim size	W9
Permitted rim size	11
Maximum air pressure [bar].	4,90
Section width (mm)	308
Outer diameter of tyre [mm].	965
Stat. radius (SLR) [mm]	432
Rolling circumference [mm].	2827
Tread depth (mm)	11,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 A8	3150	40	Free Rolling	4,90	LLV
	4410	10	Free Rolling	4,90	LLV