

TYRES

Product group	Tyres
Item number	15711930
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	129 A8 / 142 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15711930
EAN	8903094018789
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	129 A8 / 142 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	41,99
Recommended rim size	9
Permitted rim size	11
Maximum air pressure [bar].	3,70
Section width (mm)	308
Outer diameter of tyre [mm].	987
Stat. radius (SLR) [mm]	438
Rolling circumference [mm].	2892
Tread depth (mm)	28,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
129 A8	1850	40	Drive Wheel	3,70	LLV
142 A8	2650	40	Free Rolling	3,70	LLV