

TYRES

Product group	Tyres	
Item number	15711935	
Valid tyre size	12.5 / 80 - 18	
LI / SI / PR	135 A8 / 148 A8, 16 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	AS 504	





Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting



Technical Informations

Item number	15711935
EAN	8903094027262
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	135 A8 / 148 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	42,97
Recommended rim size	9
Permitted rim size	11
Maximum air pressure [bar].	4,90
Section width (mm)	308
Outer diameter of tyre [mm].	987
Stat. radius (SLR) [mm]	438
Rolling circumference [mm].	2892
Tread depth (mm)	28,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 A8	2180	40	Drive Wheel	4,90	LLV
148 A8	3150	40	Free Rolling	4,90	LLV

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.