

TYRES

Product group	Tyres
Item number	15711938
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	138 A8 / 150 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15711938
EAN	8903094031252
Valid tyre size	12.5 / 80 - 18
LI / SI / PR	138 A8 / 150 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	45,99
Recommended rim size	W9
Permitted rim size	9, 11
Maximum air pressure [bar].	5,50
Section width (mm)	308
Outer diameter of tyre [mm].	987
Stat. radius (SLR) [mm]	438
Rolling circumference [mm].	2892
Tread depth (mm)	27,5
Number of lugs	16x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 A8	2360	40	Drive Wheel	5,50	
150 A8	3350	40	Free Rolling	5,50	