

## TYRES

Product group	Tyres
Item number	15712355
Valid tyre size	13.0 / 65 - 18
LI / SI / PR	144 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

## Technical Informations

Item number	15712355
EAN	8903094009800
Valid tyre size	13.0 / 65 - 18
LI / SI / PR	144 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 702
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	33,68
Recommended rim size	11.0
Maximum air pressure [bar].	4,90
Section width (mm)	336
Outer diameter of tyre [mm].	890
Stat. radius (SLR) [mm]	398
Rolling circumference [mm].	2608
Tread depth (mm)	11,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		4,90	