

TYRES

Product group	Tyres
Item number	15712365
Valid tyre size	14.5 / 80 - 18
LI / SI / PR	155 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	AW 702



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

Technical Informations

Item number	15712365
EAN	8903094034666
Valid tyre size	14.5 / 80 - 18
LI / SI / PR	155 A8, 12 PR
TL/TT	TT
Brand	BKT
Tread pattern	AW 702
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	50,37
Recommended rim size	11.0
Permitted rim size	12, 13
Maximum air pressure [bar].	4,50
Section width (mm)	362
Outer diameter of tyre [mm].	1047
Stat. radius (SLR) [mm]	446
Rolling circumference [mm].	3068
Tread depth (mm)	16,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40		4,50	