

## **TYRES**

Product group	Tyres	
Item number	15712382	
Valid tyre size	15.0 / 70 - 18	
LI / SI / PR	151 A8, 16 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	AW 705	





## Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field



## **Technical Informations**

Item number	15712382
EAN	8903094025749
Valid tyre size	15.0 / 70 - 18
LI / SI / PR	151 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 705
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	47,75
Recommended rim size	13.00
Permitted rim size	13, W13
Maximum air pressure [bar].	4,25
Section width (mm)	405
Outer diameter of tyre [mm].	1010
Stat. radius (SLR) [mm]	447
Rolling circumference [mm].	3092
Tread depth (mm)	12,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40	Free Rolling	4,21	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.