Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres	
Item number	15712392	
Valid tyre size	250 / 80 - 18	
LI / SI / PR	115 A8 / 127 A8, 8 PR	
TL/TT	тт	
Brand	ВКТ	
Tread pattern	Farm 2000	





Notes and features

• High tractive power

• Wide contact area

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15712392
EAN	8903094040285
Valid tyre size	250 / 80 - 18
LI / SI / PR	115 A8 / 127 A8, 8 PR
TL/TT	Π
Brand	ВКТ
Tread pattern	Farm 2000
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	23,21
Recommended rim size	W8
Permitted rim size	W7, W9
Maximum air pressure [bar].	2,80
Section width (mm)	240
Outer diameter of tyre [mm].	870
Stat. radius (SLR) [mm]	394
Rolling circumference [mm].	2679
Tread depth (mm)	32,5
Number of lugs	17x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
115 A8	1215	40	Drive Wheel	2,80	LLV
127 A8	1750	40	Free Rolling	2,80	LLV

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.