

TYRES

| Product group | Tyres | |
|-----------------|-----------------------|--|
| Item number | 15712392 | |
| Valid tyre size | 250 / 80 - 18 | |
| LI / SI / PR | 115 A8 / 127 A8, 8 PR | |
| TL/TT | тт | |
| Brand | BKT | |
| Tread pattern | Farm 2000 | |





Notes and features

• High tractive power

Wide contact area



Technical Informations

| Item number | 15712392 |
|------------------------------|-----------------------|
| EAN | 8903094040285 |
| Valid tyre size | 250 / 80 - 18 |
| LI / SI / PR | 115 A8 / 127 A8, 8 PR |
| TL/TT | тт |
| Brand | BKT |
| Tread pattern | Farm 2000 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 23,21 |
| Recommended rim size | W8 |
| Permitted rim size | W7, W9 |
| Maximum air pressure [bar]. | 2,80 |
| Section width (mm) | 240 |
| Outer diameter of tyre [mm]. | 870 |
| Stat. radius (SLR) [mm] | 394 |
| Rolling circumference [mm]. | 2679 |
| Tread depth (mm) | 32,5 |
| Number of lugs | 17x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 115 A8 | 1215 | 40 | Drive Wheel | 2,80 | LLV |
| 127 A8 | 1750 | 40 | Free Rolling | 2,80 | LLV |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.