

TYRES

Product group	Tyres
Item number	15712410
Valid tyre size	19.0 / 45 - 17
LI / SI / PR	138 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 708



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction.
- Good handling characteristics, both on the road and in the field.

Technical Informations

Item number	15712410
EAN	8903094010233
Valid tyre size	19.0 / 45 - 17
LI / SI / PR	138 A8, 10 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 708
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	39,25
Recommended rim size	16.00
Maximum air pressure [bar].	2,25
Section width (mm)	491
Outer diameter of tyre [mm].	866
Stat. radius (SLR) [mm]	380
Rolling circumference [mm].	2536
Tread depth (mm)	12,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 A8	2360	40		3,00	