

## TYRES

|                 |                        |
|-----------------|------------------------|
| Product group   | Tyres                  |
| Item number     | 15712419               |
| Valid tyre size | 19.0 / 45 - 17         |
| LI / SI / PR    | 134 A8 / 147 A8, 16 PR |
| TL/TT           | TL                     |
| Brand           | BKT                    |
| Tread pattern   | AS 504                 |



## Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

## Technical Informations

|                              |                        |
|------------------------------|------------------------|
| Item number                  | 15712419               |
| EAN                          | 8903094064465          |
| Valid tyre size              | 19.0 / 45 - 17         |
| LI / SI / PR                 | 134 A8 / 147 A8, 16 PR |
| TL/TT                        | TL                     |
| Brand                        | BKT                    |
| Tread pattern                | AS 504                 |
| Antistatic                   | No                     |
| Tyre colour                  | Black                  |
| ECE regulation number        | ECE 106                |
| Nettogewicht [kg] (gültig)   | 43,85                  |
| Recommended rim size         | 16.00                  |
| Maximum air pressure [bar].  | 3,10                   |
| Section width (mm)           | 465                    |
| Outer diameter of tyre [mm]. | 865                    |
| Stat. radius (SLR) [mm]      | 389                    |
| Speed Radius Index (SRI)     | 410                    |
| Rolling circumference [mm].  | 2578                   |
| Tread depth (mm)             | 25,0                   |
| Number of lugs               | 18x2                   |
| E-Ready                      | No                     |

## Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 134 A8 | 2120               | 40           | Drive Wheel   | 3,10                     | LLV          |
| 147 A8 | 3075               | 40           | Free Rolling  | 3,10                     | LLV          |