

TYRES

Product group	Tyres
Item number	15712419
Valid tyre size	19.0 / 45 - 17
LI / SI / PR	134 A8 / 147 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504



Bohnenkamp
Moving Professionals



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15712419
EAN	8903094064465
Valid tyre size	19.0 / 45 - 17
LI / SI / PR	134 A8 / 147 A8, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	43,85
Recommended rim size	16.00
Maximum air pressure [bar].	3,10
Section width (mm)	465
Outer diameter of tyre [mm].	865
Stat. radius (SLR) [mm]	389
Speed Radius Index (SRI)	410
Rolling circumference [mm].	2578
Tread depth (mm)	25,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
134 A8	2120	40	Drive Wheel	3,10	LLV
147 A8	3075	40	Free Rolling	3,10	LLV