

TYRES

Product group	Tyres
Item number	15712429
Valid tyre size	500 / 50 - 17
LI / SI / PR	145 A8 / 157 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648



Notes and features

- Bias flotation tyre for mixed use in fields and on roads
- Can be used universally on various agricultural trailers and towed equipment
- Developed for high load capacities, even with low inflation pressure, therefore minimised ground pressure
- Rounded shoulders provide additional protection for green areas and plant stock
- Traction tread pattern with overlapping lugs for good self-cleaning and smooth running

Technical Informations

Item number	15712429
EAN	8903094040346
Valid tyre size	500 / 50 - 17
LI / SI / PR	145 A8 / 157 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	58,71
Recommended rim size	16.00
Maximum air pressure [bar].	4,00
Section width (mm)	510
Outer diameter of tyre [mm].	945
Stat. radius (SLR) [mm]	416
Rolling circumference [mm].	2750
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40	Drive Wheel	4,00	
157 A8	4125	40	Free Rolling	4,00	