

## TYRES

Product group	Tyres
Item number	15712436
Valid tyre size	500 / 50 - 17
LI / SI / PR	149 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 708



## Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction.
- Good handling characteristics, both on the road and in the field.

## Technical Informations

Item number	15712436
EAN	8903094010370
Valid tyre size	500 / 50 - 17
LI / SI / PR	149 A8, 14 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 708
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	54,85
Recommended rim size	16.00
Maximum air pressure [bar].	2,80
Section width (mm)	500
Outer diameter of tyre [mm].	945
Stat. radius (SLR) [mm]	416
Rolling circumference [mm].	2750
Tread depth (mm)	12,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		2,80	LLV