

## TYRES

Product group	Tyres
Item number	15712439
Valid tyre size	500 / 65 - 17
LI / SI / PR	160 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 708



## Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction.
- Good handling characteristics, both on the road and in the field.

## Technical Informations

Item number	15712439
EAN	8903094034307
Valid tyre size	500 / 65 - 17
LI / SI / PR	160 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 708
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	62,66
Recommended rim size	16.0
Maximum air pressure [bar].	3,50
Section width (mm)	520
Outer diameter of tyre [mm].	1070
Stat. radius (SLR) [mm]	462
Rolling circumference [mm].	3135
Tread depth (mm)	13,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		3,50	LLV