

## TYRES

Product group	Tyres
Item number	15712445
Valid tyre size	6.50 - 20
LI / SI / PR	112 A6, 10 PR
TL/TT	TT
Brand	BKT
Tread pattern	BK 308



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The BK 308 tread pattern provides excellent traction and good running characteristics in transport applications
- The strong casing provides high durability and protects the tyre against puncture damages
- Its special rubber compound ensures a long service life

## Technical Informations

Item number	15712445
EAN	8903094044993
Valid tyre size	6.50 - 20
LI / SI / PR	112 A6, 10 PR
TL/TT	TT
Brand	BKT
Tread pattern	BK 308
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	19,07
Recommended rim size	5.50F
Permitted rim size	4.00E, 5.00F
Maximum air pressure [bar].	4,80
Section width (mm)	190
Outer diameter of tyre [mm].	865
Stat. radius (SLR) [mm]	393
Rolling circumference [mm].	2534
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
112 A6	1120	30		4,80	