

TYRES

Product group	Tyres
Item number	15712471
Valid tyre size	16.0 / 70 - 20
LI / SI / PR	151 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 705



Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction
- Good handling characteristics, both on the road and in the field

Technical Informations

Item number	15712471
EAN	8903094027408
Valid tyre size	16.0 / 70 - 20
LI / SI / PR	151 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 705
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	46,32
Recommended rim size	13.0
Permitted rim size	12 SDC, 13 SDC, 14
Maximum air pressure [bar].	3,00
Section width (mm)	408
Outer diameter of tyre [mm].	1075
Stat. radius (SLR) [mm]	480
Rolling circumference [mm].	3155
Tread depth (mm)	13,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40		3,00	