

TYRES

| | |
|-----------------|------------------------|
| Product group | Tyres |
| Item number | 15712480 |
| Valid tyre size | 16.0 / 70 - 20 |
| LI / SI / PR | 135 A8 / 147 A8, 10 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | AS 504 |



Bohnenkamp
Moving Professionals



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

| | |
|------------------------------|------------------------|
| Item number | 15712480 |
| EAN | 8903094019021 |
| Valid tyre size | 16.0 / 70 - 20 |
| LI / SI / PR | 135 A8 / 147 A8, 10 PR |
| TL/TT | TL |
| Brand | BKT |
| Tread pattern | AS 504 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 62,35 |
| Recommended rim size | 13 |
| Permitted rim size | 12SDC, 14, 13SDC |
| Maximum air pressure [bar]. | 2,50 |
| Section width (mm) | 408 |
| Outer diameter of tyre [mm]. | 1097 |
| Stat. radius (SLR) [mm] | 487 |
| Rolling circumference [mm]. | 3214 |
| Tread depth (mm) | 31,0 |
| Number of lugs | 16x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 135 A8 | 2180 | 40 | Drive Wheel | 2,50 | LLV |
| 147 A8 | 3075 | 40 | Free Rolling | 2,50 | LLV |