

TYRES

Product group	Tyres
Item number	15712486
Valid tyre size	400 / 70 - 20
LI / SI / PR	149 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504



Bohnenkamp
Moving Professionals



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15712486
EAN	8903094035236
Valid tyre size	400 / 70 - 20
LI / SI / PR	149 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	63,43
Recommended rim size	13
Permitted rim size	12SDC, 14, 13SDC
Maximum air pressure [bar].	4,00
Section width (mm)	408
Outer diameter of tyre [mm].	1097
Stat. radius (SLR) [mm]	487
Rolling circumference [mm].	3214
Tread depth (mm)	31,0
Number of lugs	16x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 A8	3250	40		4,00	