

## TYRES

Product group	Tyres
Item number	15712488
Valid tyre size	400 / 55 - 22.5
LI / SI / PR	154 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 705



## Notes and features

- Implement tyre with grooved farm trailer tread pattern for trailers and other towed agricultural machines such as balers, spreaders, etc.
- Allows high load capacities with low soil compaction.
- Good handling characteristics, both on the road and in the field.

## Technical Informations

Item number	15712488
EAN	8903094042449
Valid tyre size	400 / 55 - 22.5
LI / SI / PR	154 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	AW 705
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	51,16
Recommended rim size	11.75
Maximum air pressure [bar].	4,50
Section width (mm)	405
Outer diameter of tyre [mm].	1016
Stat. radius (SLR) [mm]	443
Rolling circumference [mm].	3072
Tread depth (mm)	13,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 A8	3750	40		4,50	