

TYRES

Product group	Tyres
Item number	15712490
Valid tyre size	400 / 80 - 24
LI / SI / PR	162 A8
TL/TT	TL
Brand	BKT
Tread pattern	AS 504



Bohnenkamp
Moving Professionals



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15712490
EAN	8903094035267
Valid tyre size	400 / 80 - 24
LI / SI / PR	162 A8
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	76,42
Recommended rim size	W13
Permitted rim size	W12, W14L
Maximum air pressure [bar].	5,00
Section width (mm)	394
Outer diameter of tyre [mm].	1262
Stat. radius (SLR) [mm]	566
Rolling circumference [mm].	3655
Tread depth (mm)	40,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A8	4750	40		5,00	