

TYRES

Product group	Tyres
Item number	15712494
Valid tyre size	15.5 / 80 - 24
LI / SI / PR	151 A6, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Grip Star



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- Recommended for loaders
- Sturdy nylon casing
- Enquire for weight specifications (kg) for load bearing and steering wheel

Technical Informations

Item number	15712494
EAN	8903094019762
Valid tyre size	15.5 / 80 - 24
LI / SI / PR	151 A6, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Grip Star
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	75,75
Recommended rim size	W12
Permitted rim size	W13, W14L
Maximum air pressure [bar].	5,20
Section width (mm)	392
Outer diameter of tyre [mm].	1270
Stat. radius (SLR) [mm]	569
Rolling circumference [mm].	3683
Tread depth (mm)	40,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A6	3450	30		5,20	