

TYRES

Product group	Tyres
Item number	15712495
Valid tyre size	15.5 / 80 - 24
LI / SI / PR	145 A8 / 157 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504



Notes and features

- The BKT AS 504 is a versatile agro-industrial tyre for transport and soil cultivation
- It is characterised by excellent self-cleaning properties and increased adhesion, ideally suited for use on muddy ground
- Some sizes were developed for loading work and for use in hay harvesting

Technical Informations

Item number	15712495
EAN	8903094018963
Valid tyre size	15.5 / 80 - 24
LI / SI / PR	145 A8 / 157 A8, 12 PR
TL/TT	TL
Brand	BKT
Tread pattern	AS 504
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	72,22
Recommended rim size	W12
Permitted rim size	W13, W14L
Maximum air pressure [bar].	3,00
Section width (mm)	384
Outer diameter of tyre [mm].	1262
Stat. radius (SLR) [mm]	570
Rolling circumference [mm].	3875
Tread depth (mm)	40,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40	Drive Wheel	3,00	LLV
157 A8	4125	40	Free Rolling	3,00	LLV